



OFFSHORE



LAND RIG

**Gates Black Gold®
Cementing Hose
(With Fluoroelastomer Tube)
15,000 psi W.P. - 22,500 psi Test
33,750 Minimum Burst**

Certification/Standards

- Coupling/Mat'l Traceability (Additional Cost)
- Letter of Conformance (Additional Cost)
- Test Certificates
- 3rd Party Witness Test (Additional Cost)



(Shown with hub fitting)

Specification 4758L

RECOMMENDED FOR: Used as a flexible connection between the cementing pump manifold and cementing head for conveyance of cement slurries at high pressure.

TEMPERATURE: -4°F to +212°F (-20°C to +100°C).

TUBE: Type V (Fluoroelastomer). Black. Excellent resistance to abrasion and corrosion.

REINFORCEMENT: Multiple layers of "close wound", high tensile plated steel cables to withstand flexing and high pressures encountered in offshore operations. Multiple layers of fabric reinforcement under cover.

COVER: Type C₄ (Modified Nitrile). Black. Specially compounded UltraBration cover is resistant to abrasion, corrosion, cutting, gouging, oil and weather. One continuous longitudinal yellow transfer label. Serial number and manufacture date embossed.

COUPLINGS: Special Built-In supplied with your choice of end fittings, (see "Most Commonly used Welded-On Fittings" section for more detailed information).

NOTE: FIELD WELDING OF FITTINGS TO COUPLING IS **NOT** RECOMMENDED.

FITTINGS: Hammer Unions

Hubs

Flanges



Female Sub Male Sub./Nut



AVAILABLE SIZES:

Available Sizes (Inches)	2-1/2	3	Spec.
Nom. O.D.	5.66	6.16	4758L
Min. Bend Radius (Inches)	60	60	
Wt. per Ft. of hose (Lbs)	29.4	33.2	
Coupling. Wts. Each (Lbs)	130	172	
Maximum length of hose (Feet)	90	90	
Safety Clamp & Chain Part No.	7361-0840	7361-0845	

OPTIONAL: Accessories such as SAFETY CLAMPS, HOSE LIFT EYE & COLLAR CLAMP and STAINLESS STEEL ARMOR are found on page 53.